

	Bulletin 855P — Panel Mount Signaling Products • Mounts in Standard 22.5 mm Hole • Watertight Panel Alarms in 3 Different Sizes • Sound Output Ranging from 80 dB @ 1 Meter to 105 dB @ 1 Meter • IP65 Environmental Rating • UL Type 4/4X/13 • Selectable Continuous or Pulsing Tone on 30 mm and 45 mm • Selectable Continuous, Wobble or Pulsing Tone on 65 mm • Combination Sounder and LED products • Panel Mount Strobe or LED Indicator products • Plug-in Terminal Blocks, IP2X Rated	Table of Contents Product Selection this page Accessories..... 6 Specifications..... 7 Approximate Dimensions..... 8 Standards Compliance and Certifications EN 60947-5-1 EN 61000-6-2 EN 50081-2 UL 508 CSA 22.2 No. 14 cULus Listed (File No. E14840, Guide No. NKCR) CE Marked
---	---	---

Product Selection

Bulletin 855P — Panel Mount Sounder

855P – $\frac{B}{a}$ $\frac{10}{b}$ $\frac{ME}{c}$ $\frac{22}{d}$



30 mm Panel Mount Sounder 45 mm Panel Mount Sounder 65 mm Panel Mount Sounder

a

Housing Color	
Code	Description
B	Black

b

Voltage	
Code	Description
30	12...24V AC/DC
10	120V AC
20	240V AC

c

Size	
Code	Description
SE	30 mm
ME	45 mm
LE	65 mm

d

Mounting Hole	
Code	Description
22	22.5 mm

Housing Color	Voltage	Size	Cat. No.
Black	12...24V AC/DC	30 mm	855P-B30SE22
		45 mm	855P-B30ME22
		65 mm	855P-B30LE22
	120V AC	30 mm	855P-B10SE22
		45 mm	855P-B10ME22
		65 mm	855P-B10LE22