

CENTER 315/316 HUMIDITY TEMPERATURE METER



CE

Features:

- Dew Point and Wet Bulb Temperature Measurement. (316)
- Fast response.
- Auto shut off for Battery Saving.
- REL Function. (315)
- MAX/MIN Function.
- Dual displays:
Primary display for Humidity;
Secondary displays for Temperature.

CENTER®

CENTER 315/316 HUMIDITY TEMPERATURE METER

FEATURE

- Dew Point and Wet Bulb temperature Measurement.(316)
- Fast response.
- Auto shut off for Battery Saving.
- REL Function.(315)
- MAX/MIN Function.
- Dual displays:
Primary display for Humidity; Secondary displays for temperature.

SPECIFICATIONS

- **Measurement Range:**
Temperature: $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$; $-4^{\circ}\text{F} \sim 140^{\circ}\text{F}$
Humidity: 0%RH~100%RH
- **Resolution:**
 $0.1^{\circ}\text{C}/0.1^{\circ}\text{F}/0.1\%\text{RH}$
- **Accuracy:**
Temperature: $\pm 0.8^{\circ}\text{C}$, 1.6°F
Humidity: $\pm 3.0\%\text{RH}$
- **Sampling Rate:** 2 times/sec
- **Battery Type:**
9V, NEDA 1604, IEC 6F22, JIS 006P
- **Operating Condition:**
 0°C to 40°C ($<80\%\text{RH}$)
- **Dimensions:**
 $240 \times 54 \times 34 \text{ mm}$
- **Accessories:**
Battery, Instruction Manual

**33%RH / 75%RH
Humidity Standard
(OPTIONAL)**



Dual Display

CENTER 315



CENTER 316



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®

CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com

Distributed by: