

Standard Type

high voltage

Powerful into action

produced by translucent PP
material, Easy maintenance. ..

+ Specifications

Assembly Fig

New Model	Model	C.C.A	Nominal Voltage (V)	Capacity (AH)		Dimensions (mm)			Weight with Acid approx. (KG)	Weight without Acid approx. (KG)	Electrolyte approx.(L)	Regular charge current(A)	Terminal Layout		
				5 HR	20 HR	(L)	(W)	(H)					Layout	Terminal	
26A19L	12N24-3	201	12	21	26	184	124	162	179	-	5.2	1.5	2.6	2	Z
26A19R	12N24-4	201	12	21	26	184	124	162	178	-	5.2	1.5	2.6	1	Z
28B19L	-	190	12	24	30	187	127	202	227	-	6.9	2.4	3.0	2	Y
34B19L	NS40ZAL	240	12	27	33	185	125	202	224	-	6.6	2.3	3.3	2	Y
34B19L(S)	NS40ZAL(S)	240	12	27	33	185	125	202	224	-	6.6	2.3	3.3	2	A
34B19R(S)	NS40ZA(S)	240	12	27	33	185	125	202	224	-	6.6	2.3	3.3	1	A
36B20L	NS40ZL	260	12	28	35	195	127	202	225	-	7.6	2.2	3.5	2	Y
36B20R	NS40Z	260	12	28	35	195	127	202	225	-	7.6	2.2	3.5	1	Y
36B20R(S)	NS40Z(S)	260	12	28	35	195	127	202	225	-	7.6	2.2	3.5	1	A
38B19L	-	-	12	28	35	185	125	202	224	9.2	-	-	3.5	2	Y
38B19L(S)	-	-	12	28	35	185	125	202	224	9.2	-	-	3.5	2	A
38B19R	-	-	12	28	35	185	125	202	224	9.2	-	-	3.5	1	Y
38B19R(S)	-	-	12	28	35	185	125	202	224	9.2	-	-	3.5	1	A
46B24L	NS60L	295	12	36	45	236	127	202	225	-	8.6	2.8	4.5	2	Y
46B24L(S)	NS60L(S)	295	12	36	45	236	127	202	225	-	8.6	2.8	4.5	2	A
46B24R	NS60	295	12	36	45	236	127	202	225	-	8.6	2.8	4.5	1	Y
46B24R(S)	NS60(S)	295	12	36	45	236	127	202	225	-	8.6	2.8	4.5	1	A
48D26L	N50L	250	12	40	50	258	171	202	223	-	9.5	4.3	5.0	2	A

48D26R	N50	250	12	40	50	258	171	202	223	-	9.5	4.3	5.0	1	A
55B24R(S)	-	370	12	36	45	236	127	202	225	-	8.7	2.8	4.5	1	A
55B24L(S)	-	-	12	36	45	236	127	202	225	-	8.7	2.8	4.5	2	A
55D23L	-	320	12	48	60	230	171	202	223	-	10.8	3.7	6.0	2	A
55D23R	-	-	12	48	60	230	171	200	223	15.5	-	-	6	1	A
55D26L	N50ZL	290	12	48	60	258	171	202	223	-	11.2	4.4	6.0	2	A
55D26R	N50Z	290	12	48	60	258	171	202	223	-	11.2	4.4	6.0	1	A
65D23R	-	370	12	52	65	230	171	202	223	-	12.5	3.5	6.5	1	A
65D26R	NS70	370	12	52	65	258	171	202	222	-	11.2	4.3	6.5	1	A
65D26L	-	-	12	52	65	258	171	200	222	16.8	-	-	6.5	2	A
65D31L	N70L	340	12	56	70	303	171	202	223	-	12.6	5.8	7.0	2	A
65D31R	N70	340	12	56	70	303	171	202	223	-	12.6	5.4	7.0	1	A
75D23L	-	465	12	52	65	230	171	202	223	-	12.5	3.5	6.5	2	A
75D23R	-	465	12	52	65	230	171	202	223	-	12.5	3.5	6.5	1	A
75D31R	N70Z	380	12	60	75	303	171	202	223	-	14.6	4.8	7.5	1	A
80D26L	-	490	12	55	68	257	170	202	222	-	14.2	4.0	6.5	2	A
80D26R	NX110-5	490	12	55	68	257	170	202	222	-	14.2	4.0	6.5	1	A
95D31R	NX120-7	565	12	64	80	303	171	202	223	-	15.7	4.8	8.0	1	A
95D31L	-	-	12	64	80	303	171	200	223	21.8	-	-	8.0	2	A
115D31L	-	650	12	70	88	303	171	200	223	22.62	-	-	8.8	2	A
95E41R	N100	475	12	80	100	407	173	211	234	-	17.3	6.9	10.0	1	A
115E41R	NS120	610	12	88	110	407	173	211	234	-	19.4	6.5	11.0	1	A
130E41L	-	680	12	92	115	407	173	234	234	-	21.4	8.0	11.5	2	A
115F51	N120	575	12	96	120	502	180	212	225	-	22.1	8.8	12.0	3	A
145F51	NS150	735	12	112	140	502	180	212	255	-	26.1	8.3	14.0	3	A
150F51	-	-	12	112	140	502	180	212	255	-	26.1	8.3	14	3	A
145G51	N150	685	12	120	150	505	220	212	255	-	28.9	10.0	15.0	3	A
190H52	N200	765	12	160	200	518	276	219	266	-	37.0	14.2	20.0	3	A
3-75	4H	-	6	120	150	300	169	202	223	-	12.8	5.1	15.0	7	A
55548	-	255	12	-	55	246	175	190	190	-	10.8	3.1	5.5	1	A
55530	-	255	12	-	55	246	175	190	190	-	10.8	3.1	5.5	2	A
56224	-	-	12	-	62	246	175	190	190	-	11.5	3.1	6.2	2	A
56618	-	300	12	-	66	306	175	190	190	-	14.4	3.7	6.6	2	A
56619	-	300	12	-	66	306	175	190	190	-	14.4	3.7	6.6	2	F
56801-MF	-	-	12	-	68	311	174	174	174	21.1	-	-	6.8	2	A
57219	-	420	12	-	72	306	175	190	190	-	15.8	3.6	7.2	1	A
57531	-	350	12	-	75	306	175	190	190	-	15.8	3.6	7.5	2	A

58014-MF	-	-	12	-	80	311	174	174	174	19.7	-	-	6.8	2	A
58815	-	395	12	-	88	381	175	190	190	-	16.5	4.8	8.8	2	A
60044	-	450	12	-	100	352	175	190	190	-	18.6	4.5	10.0	2	A
61023	-	450	12	-	110	514	175	210	210	-	22.5	8.0	11.0	4	A
64323	-	570	12	-	143	514	218	210	210	-	26.9	9.9	14.3	4	A
R2-600R	-	-	12	-	66	277	174	174	174	18.4	-	-	6.6	2	A
SB175	-	-	6	140	175	405	174	207	258	-	19.6	27	17.5	7	F