


ACESEE

◆ SPECIFICATION

Model NO.	ADST20E200	ADST20P200	ADST20H200	ADST20M130	ADST20H130	ADST20H100
Camera						
Image Sensor	IMX222	IMX22	IMX222	IMX238	IMX238	OV9712S
Main processor	A5S66	DM368	HI3516C	DM365	HI3518C	HI3518E
Resolution	1080P	1080P	1080P	960P	960P	720P
Effective Pixels	1920(H)*1080(V)	1920(H)*1080(V)	1920(H)*1080(V)	1280(H)*960(V)	1280(H)*960(V)	1280(H)*720(V)
TV System	PAL/NTSC					
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec					
Sync System	External					
Usable Illumination	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.1Lux
S/N Ratio	≥52dB					
Scanning System	Progressive					
Video Output	Network					
Lens						
Focus Length	3.6mm					
Focus Control	Fixed					
Lens Type	Fixed					
Pixels	3M Pixels	3M Pixels	3M Pixels	2M Pixels	2M Pixels	2M Pixels
Night Vision						
Infrared LED	Φ 5X24PCS					
Infrared Distance	20M					
IR Status	Under 10 Lux By CDS					
IR Power On	CDS Auto Control					
Network						
Ethernet	RJ-45 (10/100Base-T)					
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS					
ONVIF	Support ONVIF 2.4					
P2P	YES, Support QR Code					
POE	Optional, Support IEEE 802.3af					
WIFI	N/A					
Video Delay	0.3S (Within the Lan)					
Main Stream	1920*1080	1920*1080	1920*1080	1280*960	1280*960	1280*720
Sub Stream	704*576, 352*288	704*576, 352*288	704*576, 352*288	704*576, 352*288	704*576, 352*288	704*576, 352*288
IE Brower	IE6-11					
Smart Phone	iPhone, iPad, Android, Android Pad					
Camera Features						
Day/Night	Color/ B&W (IR-CUT)					
Compression	H.264/JPEG,Support record AVI format.					
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)					
Motion Detection	Support					
Privacy Masking	3 Rectangular Zone					
WDR	YES	NO	NO	NO	NO	NO
Recording Mode	NVR/NAS/CMS/Web					
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian					
General						
Housing	Vandalproof(metal)					
Lens Angle Adjustment	NO,Without Bracket					
IR Cut Filter	YES					
Operation Temperature	-10℃ ~ +50℃ RH95% Max					
Storage Temperature	-20℃ ~ +60℃ RH95% Max					
Power Source	DC12V±10%, 700mA					
Dimension	Φ 94 x 69(H)mm					
Weight	400g					